

THE FIXNET® SAVES TIME AND EASILY DISMOUNTS THE NET.

FIXNET® is very discreet, fast to install, very economical.

It is not necessary to drill, except in case of damage or porous surfaces. Economy rope, net stapler, staples, turnbuckle... Not damage surfaces.

MAIN FEATURES:

- Oxygen resistance, ultraviolet resistance, alkaline salt resistance .
- · Bad solvent resistance, do not use damp-proofing product in pulverizing.
- Adhesion: use a polyurethane glue or double tape adhesive, granitic areas for a maximal adhesion.
- Double tape adhesive only supplied by **ECOPIC**.

TECHNICAL DATAS FIXNET :

- Material: 100 % virgin Polycarbonate, anti-uv traited in the mass.
- Dimension: 30 x 35 mm • Thickness: max 10 mm

FIXNET BOX COMPOSITION:

• A bag of FIXNET® includes 500 pieces.

ECOPIC® ADVICE:

- All areas low/moderate/strong pressure.
- · When a location is occupied by birds, pay attention of the mesh choice according to the birds size.
- A 5 x 5 meters net, (50 mm mesh or 19 mm mesh size), needs approximately 100 FIXNET®

Fitting informations:

- · Optimal climatic conditions
 - Maintain temperature between + 5°C and + 30 °C.
 - · Shielded from the rain.
- Support preparation
 - Remove the dust (if necessary dry-clean, brush).
 - Support should be dry. If necessary, apply a primer on porous surfaces.

Cleaning: For a better guarantee, clean with SELCLEANING®, (natural cleaner)

Guarantee: Refer to the conditions defined in our brochure or website

WHERE INSTALLING:

- · All types of buildings, statues, museums, factories, schools, balconies, railings, courtyard, windows, doors, balconies...
- The support must be clean, dry, healthy, solid.

MANUAL:

· See installation sheet